

Smarter, Better, Stronger!









Highlights

Extreme workload range of 10 - 3000 watt

This extraordinary peak workload is extremely suitable for sports medicine and testing the strongest athletes on their anaerobic power or isokinetic capacity. Combined with the low start workload of 10 Watt this Excalibur will fit everybody.

Left and right independent measurements

The PFM is not only the summation of left and right, but real left and right independent measurements. Differences between the left and right pedal movement, before and after surgery or at different workload can be detected. A real diagnostic tool!

Measurement every 2 degrees

The accuracy of the PFM during the total revolution is obtained by the placement of highly specific strain gauges in the crank axis making it possible to measure the pedal force every 2 degrees during each revolution during the exercise test.

Special Analysis and Polar Graphs

Analysis and Polar graphs are specifically designed for pedal force measurement

LEM PFM included

The LEM software with PFM module is standard included







Smarter, Better, Stronger!

With its unbeatable accuracy and reliability, the Excalibur Sport has proven itself as The Gold Standard in Ergometry ever since 1985. However, the world keeps spinning and developments never stop. That is why we now proudly present the new Lode Excalibur Sport: Smarter, Better and Stronger! Still true to its heritage but combined with innovative new features to meet the latest and future requirements of modern sports medicine and research to allow athletes to become stronger and better with smarter use of human performance technology.

Versatile ergometer

The new Lode Excalibur Sport ergometer is an essential part of a sports medicine or research lab, since it can be used to test all types of athletes. The ergometer allows for various tests, like a Wingate sprint test, Isokinetic tests, High Intensity Tests (HIT) and time trials. Moreover, it can also be used for CPET testing and bike fitting.

Pedal Force Measurement

This Excalibur sport has built-in modified strain gauge technology that measures forces exerted on the pedals during exercise and is supplied with angle detection. Independent measurements of forces in both left and right crank are possible. Wireless transmission of the measured forces to the PC by bluetooth.

Note: this setting is supplied with a 3,5" control unit, LEM and LEM PFM software (various other modules are available), a computer (we recommend to use this PC only for the LEM software) and a Network module connection cable (#930930) and a USB A-B cable to connect to cpet devices.





PFM

Smarter, Better, Stronger!

Features



Electric adjustable saddle Excalibur Sport

The position of the saddle of the excalibur sport can be adjusted in height, length and angle to suit all users.

The saddle of the ergometer can be adjusted horizontally in a range of 252 mm and the saddle height in a range of 388 mm using the Control Unit or LEM.

The Test Subject can be seated on the saddle while adjusting.



Electric adjustable handlebar Excalibur Sport

The position of the handlebar of Excalibur Sport is completely adjustable in height and length.

The handlebar of the ergometer can be adjusted horizontally in a range of 169mm and vertically in a range of 390mm using the Control Unit or LEM software. The Test Subject can use the handlebar while adjusting.



Extreme low start up load 10W

The extreme low start-up load of 10 watts and the adjustability in small steps of 1 watt make this ergometer perfectly suitable for many different applications. The standard control unit shows multiple ergometry parameters and you can determine your specific default setting and start-up menu.



Low noise

Due to accurate manufacturing and the careful choice of materials the product has an extremely low noise level.



Accurate over a long period of time

The Lode ergometers are supplied with an electro-magnetic braking mechanism of Lanooy (eddy current). The biggest advantage of this braking system compared to a friction braking system is the absolute accuracy and the accuracy over time. Moreover, friction braking systems have more wearing parts.



Compatible with ECG and pulmonary devices

The Lode ergometers have digital interfaces and can be controlled easily by all known stress ECG and pulmonary devices available in the world. This is one of the reasons why the Lode ergometers are very popular worldwide.



Exchangeable pedals

The cranks of the ergometer are suitable for almost all available clip systems so cyclists can perform a test with their own favorite pedals.



Designed to be sweat-proof

The housing of the ergometer is designed in such way that sweat does not have the chance to drip into the mechanical parts and cables are protected. This ensures a long lifetime and makes the ergometer insensitive for malfunction.



RS232 connectivity

RS232 ports enable connectivity to most ECG and ergospirometry devices as well as PC's.



LEM compatible

This product can be used with Lode Ergometry Manager (LEM) software to manage data and to apply specific protocols when a Communication card is present





Smarter, Better, Stronger!



Smarter, Better, Stronger!

SMARTER - The future is now

Adjustment of both the seat and the handlebar is possible in both a horizontal and vertical range. This adjustability can be controlled electrically through the display of the bike or LEM software, enabling easy optimization of the seating position. Moreover, the seat, handlebar and pedals can be exchanged easily for total adaption to the body posture and bike-fitting of each individual athlete.

You can extend the new Lode Excalibur Sport with the Lode Ergometry Manager Software, for faster availability of data and to simplify the analysis of the tests. The latest Lode electrics makes the ergometer ready for the future.

BETTER - It's all about the details

The adjustability range of the New Excalibur Sport has improved considerably, making it possible for even more athletes to use the bike. The new touchscreen offers an easy user interface. You can determine yourself what data is made visible.

Furthermore, blood pressure measurement and SpO2 are available.

STRONGER - No sweat, no glory

The new Lode Excalibur Sport offers the highest performance testing with an unimaginable maximum peak load of 3000 watt! This load is fully supported by the new indestructible and sweat proof design. The bike is extrenely stable and cables are protected against sweat.





PFM

Smarter, Better, Stronger!

The new Excalibur Sport with PFM can a.o be extended with the following options:

USB to Serial converter

Easy connection



Partnumber: 226012

SpO2 for control unit with touch panel (extra long cable)

Oxygen saturation



Partnumber: 945822

LEM 10 - Module Wingate Test plus


Easy to operate Sprint test for explosive



Partnumber: 955915

LEM 10 - Module Åstrand

Reproducable test



Partnumber: 955916

LEM 10 - Module Export


Export your data to MS Excel



Partnumber: 955920

LEM 10 - Module Architect


Creating protocols with customer specific



Partnumber: 955921

0-Watt start-up system

Lowest possible startup



Partnumber: 960805

Control Unit with 7" touch screen for ergometer

Multifunctionality



Partnumber: 945834

Programmable Control Unit with 7' Touchscreen for **Programm**able



Partnumber: 945835

Control Unit with touch screen 7" - ordered additionally

Multifunctionality



Partnumber: P945834

Blood Pressure with ECG trigger for bicycle ergometer

with ECG trigger



Partnumber: 945828

Saddle for children

Versatile ergometry



Partnumber: 401066

Saddle for children ordered additionally

Versatile ergometry



Partnumber: P401066

Bluetooth Smart heart rate

Heartrate available within an extreme wide



Partnumber: 945833

Packaging upgrade to wooden box

Ultra heavy duty packaging



Partnumber: U501155W





319.7 lbs

145 kg

Smarter, Better, Stronger! Specifications

Workload			User Interface		
Minimum load	10 W		English user interface	~	
Maximum peak load	3000 W		Norwegian user interface	~	
Isokinetic workload control	~		Czech user interface	~	
Minimum load increments	1 W		Danish user interface	~	
Hyperbolic workload control	~		Dutch user interface	~	
Linear workload control	~		French user interface	~	
Fixed torque workload control	~		German user interface	~	
Maximum rpm independent constant load	180 rpm		Italian user interface	~	
Minimum rpm independent constant load	30 rpm		Japanese user interface	~	
Electromagnetic "eddy current" braking system	~		Korean user interface	~	
Accuracy			Polish user interface	~	
Workload accuracy below 100 W	2 W		Portugese user interface	~	
Workload accuracy from 100 to 1500 W	2 %		Russian user interface	~	
Workload accuracy over 1500 W	5 %		Spanish user interface	~	
Comfort			Turkish user interface	~	
Toeclips on pedals	~		Ukrainian user interface	~	
Q-factor	147 mm		Terminal operation mode	~	
Minimum leg length user	737 mm	29 inch	Screen size (diagonal)	17.8 cm	7 inch
Minimum leg length user (incl. adjustable pedals)	662 mm	26.1 inch	Touchscreen	~	
Maximum leg length user	1128 mm		Connectivity		
Max. leg length user (incl. adjustable pedals)	1143 mm		Control Unit with touch screen 3,5" for ergometer	~	
Vertical seat adjustment maximum	938 mm	36.9 inch	Lode interface protocol	~	
Vertical seat adjustment minimum	550 mm	21.7 inch	Ergoline P10 interface protocol	~	
Horizontal seat adjustment minimum	72 mm	2.8 inch	Ergoline P4 interface protocol	~	
Horizontal seat adjustment maximum	324 mm	12.8 inch	Schiller interface protocol	~	
Allowed user weight	225 kg	496 lbs	Bosch EKG 506 DS interface protocol	~	
Horizontal handlebar adjustment minimum	229 mm	9 inch	USB connector	~	
Horizontal handlebar adjustment maximum	60 mm	2.4 inch	RS232 out connector	~	
Vertical handlebar adjustment minimum	465 mm	18.3 inch	Dimensions		
Vertical handlebar adjustment maximum	855 mm	33.7 inch	Product length (cm)	200 cm	78.7 inch
			Product width (cm)	70 cm	27.6 inch
			Product height	100 cm	39.4 inch
			5 1 · · · · · · · · · · · · · · · · · ·		040 = 11

Product weight





Smarter, Better, Stronger!

Power requirements

V AC	100 - 240 V	
Phases	1	
Frequency	50/60 Hz	
Power consumption	160 W	
Power cord length	250 cm	98.4 inch
Power cord IEC 60320 C13 with CEE 7/7 plug	~	

Standards & Safety

Standards & Salety	
IEC 60601-1:2012	~
ISO 13485:2016 compliant	~
ISO 9001:2015 compliant	~
Included parts	
PC included for PFM	~
Bluetooth dongle	~
Pedal Force Measurement	
Rotational measurement resolution	2°
Pedal Force accuracy	1 N

Order info

965920 Partnumber:



^{*}Specifications are subject to change without notice.